

Prepared For:
Truck Customs
Chris Walker
1020 Franke Industrial Dr.
Augusta, GA 30909-9101

Reference ID: N/A

Thank you for the opportunity to provide you with the following quotation on a new International truck. I am sure the following detailed specification will meet your operational requirements, and I look forward to serving your business needs.

Model Profile
2015 4400 SBA 4X2 (MA035)

APPLICATION:	Stake Flat
MISSION:	Requested GVWR: 33000. Calc. GVWR: 25500 Calc. Start / Grade Ability: 36.90% / 2.26% @ 55 MPH Calc. Geared Speed: 93.8 MPH 8.92 MPG @ 55 MPH
FUEL ECONOMY:	
DIMENSION:	Wheelbase: 195.00, CA: 84.00, Axle to Frame: 49.00
ENGINE, DIESEL:	{MaxxForce 9} EPA 10, 330 HP @ 2000 RPM, 950 lb-ft Torque @ 1200 RPM, 2200 RPM Governed Speed
TRANSMISSION, AUTOMATIC:	{Allison 3500_RDS_P} 5th Generation Controls; Wide Ratio, 6-Speed, With Double Overdrive; On/Off Hwy; Includes Oil Level Sensor, With PTO Provision, Less Retarder, With 80,000-lb GVW & GCW Max.
CLUTCH:	Omit Item (Clutch & Control)
AXLE, FRONT NON-DRIVING:	{Meritor MFS-08-153B} I-Beam Type, 8,000-lb Capacity
AXLE, REAR, SINGLE:	{Meritor MS-17-14X-3DCL} Single Reduction, 17,500-lb Capacity, 190 Wheel Ends, Driver Controlled Locking Differential Gear Ratio: 4.33
CAB:	Conventional 6-Man Crew Cab
TIRE, FRONT:	(2) 11R22.5 HSL2 ECO PLUS (CONTINENTAL) 500 rev/mile, load range G, 14 ply
TIRE, REAR:	(4) 11R22.5 HSL2 ECO PLUS (CONTINENTAL) 500 rev/mile, load range G, 14 ply
SUSPENSION, REAR, AIR, SINGLE:	{International} Ride Optimized Suspension (IROS); 20,000-lb Capacity, 9.25" Ride Height, With Shock Absorbers
PAINT:	Cab schematic 100GA Location 1: 9219, Winter White (Std) Chassis schematic N/A

Description

Base Chassis, Model 4400 SBA 4X2 with 195.00 Wheelbase, 84.00 CA, and 49.00 Axle to Frame.

TOW HOOK, FRONT (2) Frame Mounted

FRAME RAILS High Strength Low Alloy Steel (80,000 PSI Yield); 10.250" x 3.092" x 0.375" (260.4mm x 78.5mm x 9.5mm); 427.0" (10846mm) Maximum OAL

LICENSE PLATE HOLDER Includes Upper & Lower Mounting Plate Hardware, Mounted in Existing Holes in Front Bumper

BUMPER, FRONT Full Width, Aerodynamic, Chrome Plated Steel; 0.142" Material Thickness

BUMPER EXTENSION, FRONT 4.0"

WHEELBASE RANGE 134" (340cm) Through and Including 197" (500cm)

AXLE, FRONT NON-DRIVING {Meritor MFS-08-153B} I-Beam Type, 8,000-lb Capacity

Notes

: The following features should be considered when calculating Front GAWR: Front Axles; Front Suspension; Brake System; Brakes, Front Air Cam; Wheels; Tires.

SUSPENSION, FRONT, SPRING Parabolic, Taper Leaf; 8,000-lb Capacity; With Shock Absorbers

Includes

: SPRING PINS Rubber Bushings, Maintenance-Free

Notes

: The following features should be considered when calculating Front GAWR: Front Axles; Front Suspension; Brake System; Brakes, Front Air Cam; Wheels; Tires.

BRAKE SYSTEM, AIR Dual System for Straight Truck Applications

Includes

: BRAKE LINES Color and Size Coded Nylon
: DRAIN VALVE Twist-Type
: GAUGE, AIR PRESSURE (2) Air 1 and Air 2 Gauges; Located in Instrument Cluster
: PARKING BRAKE CONTROL Yellow Knob, Located on Instrument Panel
: PARKING BRAKE VALVE For Truck
: QUICK RELEASE VALVE Bendix On Rear Axle for Spring Brake Release: 1 for 4x2, 2 for 6x4
: SLACK ADJUSTERS, FRONT Automatic
: SLACK ADJUSTERS, REAR Automatic
: SPRING BRAKE MODULATOR VALVE R-7 for 4x2, SR-7 with relay valve for 6x4

Notes

: Front and Rear Dust Shields not Included
: Rear Axle is Limited to 19,000-lb GAWR with Code 04091 BRAKE SYSTEM, AIR and Code 04NCL BRAKES, REAR, AIR CAM Regardless of Axle/Suspension Ordered.
: Rear Axle is Limited to 20,000-lb GAWR with Code 04091 BRAKE SYSTEM, AIR and Code 04NCG BRAKES, REAR, AIR CAM Regardless of Axle/Suspension Ordered.
: Rear Axle is Limited to 23,000-lb GAWR with Code 04091 BRAKE SYSTEM, AIR and Standard Rear Air Cam Brakes Regardless of Axle/Suspension Ordered.

DRAIN VALVE {Bendix DV-2} Automatic; With Heater; for Air Tank

Includes

: DRAIN VALVE Mounted in Wet Tank

AIR BRAKE ABS {Bendix AntiLock Brake System} Full Vehicle Wheel Control System (4-Channel) With Automatic Traction Control

AIR DRYER {Bendix AD-IP} With Heater

Includes

: AIR DRYER LOCATION Inside Left Rail, Back of Cab

BRAKE CHAMBERS, FRONT AXLE {Haldex} 20 SqIn

Description

BRAKE CHAMBERS, REAR AXLE {Haldex GC3030LHDHO} 30/30 Spring Brake

Includes

: BRAKE CHAMBERS, SPRING (2) Rear Parking; WITH TRUCK BRAKES: All 4x2, 4x4; WITH TRACTOR BRAKES: All 4x2, 4x4; 6x4 & 6x6 with Rear Tandem Axles Less Than 46,000-lb. or GVWR Less Than 54,000-lb.

BRAKES, FRONT, AIR CAM S-Cam; 15.0" x 4.0"; Includes 20 Sq. In. Long Stroke Brake Chambers

Notes

: Front Axle with 14,000-lb GAWR is Limited to 13,200-lb GAWR when used in Conjunction with 15" BRAKES, FRONT, AIR CAM.

: The following features should be considered when calculating Front GAWR: Front Axles; Front Suspension; Brake System; Brakes, Front Air Cam; Wheels; Tires.

BRAKES, REAR, AIR CAM S-Cam; 16.5" x 7.0"; Includes 30/30 Sq.In. Long Stroke Brake Chamber and Spring Actuated Parking Brake

Notes

: The following features should be considered when calculating Front GAWR: Front Axles; Front Suspension; Brake System; Brakes, Front Air Cam; Wheels; Tires.

AIR COMPRESSOR {Bendix Tu-Flo 550} 13.2 CFM Capacity

AIR TANK Polished Aluminum, With Straight Thread O-Ring Ports

STEERING COLUMN Tilting and Telescoping

STEERING WHEEL 2-Spoke; 18" Diam., Black, Leather Wrapped

STEERING GEAR {TRW (Ross) THP45} Power

EXHAUST SYSTEM Single, Horizontal, Aftertreatment Device Frame Mounted Right Side Back of Cab, Includes Horizontal Tail Pipe

Includes

: NOTE: The Horizontal Tailpipe Includes a Temperature Control Device

ENGINE EXHAUST BRAKE for MaxxForce I6 Engines, Electronically Activated

SWITCH, FOR EXHAUST 3 Position, Momentary, Lighted Momentary, ON/CANCEL, Center Stable, INHIBIT REGEN, Mounted in IP Inhibits Diesel Particulate Filter Regeneration When Switch is Moved to ON While Engine is Running, Resets When Ignition is Turned OFF

ELECTRICAL SYSTEM 12-Volt, Standard Equipment

Includes

: BATTERY BOX Steel

: DATA LINK CONNECTOR For Vehicle Programming and Diagnostics In Cab

: FUSES, ELECTRICAL SAE Blade-Type

: HAZARD SWITCH Push On/Push Off, Located on Top of Steering Column Cover

: HEADLIGHT DIMMER SWITCH Integral with Turn Signal Lever

: HORN, ELECTRIC Single

: JUMP START STUD Located on Positive Terminal of Outermost Battery

: PARKING LIGHT Integral with Front Turn Signal and Rear Tail Light

: STARTER SWITCH Electric, Key Operated

: STOP, TURN, TAIL & B/U LIGHTS Dual, Rear, Combination with Reflector

: TURN SIGNAL SWITCH Self-Cancelling for Trucks, Manual Cancelling for Tractors, with Lane Change Feature

: TURN SIGNALS, FRONT Includes Reflectors and Auxiliary Side Turn Signals, Solid State Flashers; Flush Mounted

: WINDSHIELD WIPER SWITCH 2-Speed with Wash and Intermittent Feature (5 Pre-Set Delays), Integral with Turn Signal Lever

: WINDSHIELD WIPERS Single Motor, Electric, Cowl Mounted

: WIRING, CHASSIS Color Coded and Continuously Numbered

CIGAR LIGHTER Includes Ash Cup

HORN, ELECTRIC (2)

POWER SOURCE Cigar Type Receptacle without Plug and Cord

Description

RADIO Accommodation Package; Less Radio, With Wiring and Antenna, Includes Multiple Speakers

Includes

: SPEAKERS IN CAB (2) Dual-Cone with Deluxe Interior
: SPEAKERS IN CAB (4) Coaxial with Premium Interior

ALTERNATOR {Leece-Neville AVI160P2013} Brush Type; 12 Volt 160 Amp. Capacity, Pad Mount, With Remote Sense

BODY BUILDER WIRING Rear of Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/Accessory Power/Ground and Sealed Connector for Stop/Turn

BATTERY SYSTEM {International} Maintenance-Free, (2) 12-Volt 1850CCA Total

JUMP START STUD Remote Mounted

Includes

: JUMP START STUD Mounted to Battery Box

HORN, AIR ACCOMMODATION PACKAGE; less Horn

CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade

FOG LIGHTS (2) Clear, Oval, With H355W Halogen Bulb

Notes

: Fog Lights are Not Driving Lights

ENGINE SHUTDOWN Automatic; With 30 Second Delay, With International Engines

TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights

STARTING MOTOR {Delco Remy 38MT Type 300} 12 Volt; less Thermal Over-Crank Protection

INDICATOR, LOW COOLANT LEVEL With Audible Alarm

HEADLIGHT WARNING BUZZER Sounds When Head Light Switch is on and Ignition Switch is in "Off" Position

ALARM, PARKING BRAKE Electric Horn Sounds in Repetitive Manner When Vehicle Park Brake is "NOT" Set, With Ignition "OFF" and any Door Opened

HEADLIGHTS Halogen; Composite Aero Design for Two Light System

CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III With Trip Indicators, Replaces All Fuses Except For 5-Amp Fuses

GRILLE Chrome

INSULATION, UNDER HOOD for Sound Abatement

INSULATION, SPLASH PANELS for Sound Abatement

FRONT END Tilting, Fiberglass, With Three Piece Construction

PAINT SCHEMATIC, PT-1 Single Color, Design 100

Includes

: PAINT SCHEMATIC ID LETTERS "GA"

PAINT TYPE Base Coat/Clear Coat, 1-2 Tone

SAFETY TRIANGLES

SPECIAL RATING, GVWR Limited to 25,999-lb GVWR

CLUTCH Omit Item (Clutch & Control)

OIL FILTER, ENGINE {Hudgins Model 960 Spinner}

ENGINE, DIESEL {MaxxForce 9} EPA 10, 330 HP @ 2000 RPM, 950 lb-ft Torque @ 1200 RPM, 2200 RPM Governed Speed

DescriptionIncludes

: AIR COMPRESSOR AIR SUPPLY LINE Naturally-Aspirated (Air Brake Chassis Only)
: ANTI-FREEZE Red Shell Rotella Extended Life Coolant; -40 Degrees F/ -40 Degrees C; for MaxxForce Engines
: COLD STARTING EQUIPMENT Intake Manifold Electric Grid Heater with Engine ECM Control
: CRUISE CONTROL Electronic; Controls Integral to Steering Wheel
: ENGINE OIL DRAIN PLUG Magnetic
: ENGINE SHUTDOWN Electric, Key Operated
: FUEL FILTER Included with Fuel/Water Separator
: FUEL/WATER SEPARATOR Fuel/Water Separator and Fuel Filter in a Single Assembly; With Water-in-Fuel Sensor; Engine Mounted
: GOVERNOR Electronic
: OIL FILTER, ENGINE Spin-On Type
: WET TYPE CYLINDER SLEEVES

Notes

: Recommend Code 12THT when using front mount obstructions (winches, cones, reels, etc.) that restrict air flow through the radiator.

FAN DRIVE {Horton Drivemaster} Direct Drive Type, Two Speed With Residual Torque Device for Disengaged Fan Speed

Includes

: FAN Nylon

Notes

: Recommend Code 12THT when using front mount obstructions (winches, cones, reels, etc.) that restrict air flow through the radiator.

RADIATOR Aluminum; 2-Row, Cross Flow, Over Under System, 1045 SqIn Louvered, with 373 SqIn CAC, with 369 SqIn LTR, with In-Tank Transmission Oil Cooler

Includes

: DEAERATION SYSTEM with Surge Tank
: HOSE CLAMPS, RADIATOR HOSES Gates Shrink Band Type; Thermoplastic Coolant Hose Clamps
: RADIATOR HOSES Premium, Rubber

FEDERAL EMISSIONS EPA, OBD and GHG Certified for Calendar Year 2014; MaxxForce 9 & MaxxForce 10 Engines

AIR CLEANER With Service Protection Element

Includes

: GAUGE, AIR CLEANER RESTRICTION Air Cleaner Mounted

THROTTLE, HAND CONTROL Engine Speed Control; Electronic, Stationary, Variable Speed; Mounted on Steering Wheel

ENGINE CONTROL, REMOTE MOUNTED - No Provision Furnished for Remote Mounted Engine Control

ENGINE OIL SAMPLE VALVE Mounted on Engine

FAN DRIVE SPECIAL EFFECTS Fan Cooling Ring with Fan Shroud Effects, Engine Mounted

BLOCK HEATER, ENGINE {Phillips} 120 Volt/1250 Watt; With "Y" Cord From Socket in Standard Location, For a Dealer Installed Oil Pan Heater, With Extended Life Coated Metal/Plastic/Metal Material Oil Pan, for I6

Includes

: BLOCK HEATER SOCKET Receptacle Type; Mounted below Drivers Door

Notes

: MPM material is single sheet composite with two layers of sheet metal sandwiching plastic material. MPM material has electro-deposition prime coat with powder coating for the final finish coat.

BLOCK HEATER SOCKET Located on Front Bumper

EMISSION COMPLIANCE 5 Min., Tamper-Proof Engine Shutdown System, Complies With California Clean Air Regulations, Does Not Certify Engine for Low-NOx Extended Idling

TRANSMISSION, AUTOMATIC {Allison 3500_RDS_P} 5th Generation Controls; Wide Ratio, 6-Speed, With Double Overdrive; On/Off Hwy; Includes Oil Level Sensor, With PTO Provision, Less Retarder, With 80,000-lb GVW & GCW Max.

Description

TRANSMISSION SHIFT CONTROL {Allison} Push-Button Type; for Allison 3000 & 4000 Series Transmission

TRANSMISSION OIL Synthetic; 29 thru 42 Pints

AUTOMATIC NEUTRAL Allison WT Transmission Shifts to Neutral When Parking Brake is Engaged and Remains in Neutral When Parking Brake is Disengaged

ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS); General Purpose Trucks Modified for Single Input Auto Neutral

TRANSMISSION TCM LOCATION Located Inside Cab

SHIFT CONTROL PARAMETERS Allison Performance Programming in Primary and Allison Economy Programming in Secondary

SUSPENSION AIR CONTROL VALVE Pressure Release Control In Cab

AXLE, REAR, SINGLE {Meritor MS-17-14X-3DCL} Single Reduction, 17,500-lb Capacity, 190 Wheel Ends, Driver Controlled Locking Differential . Gear Ratio: 4.33

Notes

: The following features should be considered when calculating Rear GAWR: Rear Axles; Rear Suspension; Brake System; Brakes, Rear Air Cam; Brake Shoes, Rear; Special Rating, GAWR; Wheels; Tires.

: When Specifying Axle Ratio, Check Performance Guidelines and TCAPE for Startability and Performance

SUSPENSION, REAR, AIR, SINGLE {International} Ride Optimized Suspension (IROS); 20,000-lb Capacity, 9.25" Ride Height, With Shock Absorbers

Notes

: The following features should be considered when calculating Rear GAWR: Rear Axles; Rear Suspension; Brake System; Brakes, Rear Air Cam; Brake Shoes, Rear; Special Rating, GAWR; Wheels; Tires.

FUEL TANK STRAPS Bright Finish Stainless Steel, for Dual Fuel Tanks

FUEL TANK (2) Top Draw; D Style, Non Polished Aluminum, 70 U.S. Gal., 265L, Total Capacity 140 U.S. Gal., 530L; 19" Tank Depth, Mounted Under Cab Left and Right Side

Notes

: N/A with 19.5" Tires

FUEL/WATER SEPARATOR with Filter Restriction/Change Indicator, Includes Standard Equipment Water-in-Fuel Sensor

CAB Conventional 6-Man Crew Cab

Includes

: ARM REST (2) Molded Plastic; One Each Door

: CLEARANCE/MARKER LIGHTS (5) Flush Mounted

: COAT HOOK, CAB Located on Rear Wall, Centered Above Rear Window

: CUP HOLDERS Two Cup Holders, Located in Lower Center of Instrument Panel

: DOME LIGHT, CAB Rectangular, Door Activated and Push On-Off at Light Lens, Timed Theater Dimming, Integral to Console, Center Mounted

: GLASS, ALL WINDOWS Tinted

: GRAB HANDLE, CAB INTERIOR (1) "A" Pillar Mounted, Passenger Side

: GRAB HANDLE, CAB INTERIOR (2) Front of "B" Pillar Mounted, One Each Side

: GRAB HANDLE, CAB INTERIOR (4) Two Each Side, Rear Door Mounted at Hinge Side and "C" Pillar Mounted

: INTERIOR SHEET METAL Upper Door (Above Window Ledge) Painted Exterior Color

: STEP (8) Two Steps Per Door

Notes

: 43.9" CA Loss

GAUGE CLUSTER English With English Electronic Speedometer

Includes

: GAUGE CLUSTER (5) Engine Oil Pressure (Electronic), Water Temperature (Electronic), Fuel (Electronic), Tachometer (Electronic), Voltmeter

: ODOMETER DISPLAY, Miles, Trip Miles, Engine Hours, Trip Hours, Fault Code Readout

Description

: WARNING SYSTEM Low Fuel, Low Oil Pressure, High Engine Coolant Temp, and Low Battery Voltage (Visual and Audible)

GAUGE, OIL TEMP, ALLISON TRAN

GAUGE, AIR CLEANER RESTRICTION {Filter-Minder} With Black Bezel Mounted in Instrument Panel

IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster

SEAT, DRIVER {National 2000} Air Suspension, Mid Back, Vinyl, 2 Position Front Cushion Adjustment, -3 to +14 Degree Back Angle Adjust

Includes

: SEAT BELT 3-Point, Lap and Shoulder Belt Type

SEAT, PASSENGER {National 2000} Air Suspension, High Back With Integral Headrest, Vinyl, Isolated, 1 Chamber Lumbar, 2 Position Front Cushion Adjustment, -3 to +14 Degree Back Adjust

Includes

: SEAT BELT 3-Point, Lap and Shoulder Belt Type

GRAB HANDLE (2) Chrome Towel Bar Type With Anti-Slip Rubber Inserts; for Cab Entry, Mounted Left and Right, Each Side at "B" Pillar

GRAB HANDLE, ADDITIONAL EXT (2) Chrome; Towel Bar Type With Anti-Slip Rubber Inserts; Mounted Left and Right Side on Exterior, Rear of Rear Doors, With Crew Cab

MIRRORS (2) {Lang Mekra} Styled; Rectangular, 7.09" x 15.75" & Integral Convex Both Sides, 102" Inside Spacing, Breakaway Type, Heated Heads Thermostatically Controlled, Power Both Sides, Clearance Lights LED, Bright Finish Heads & Brackets

SEAT, REAR {National} BENCH; Full Width; Vinyl, With Fixed Back and Two Integral Outboard Headrests

CAB MOUNTING HEIGHT EFFECTS Mid Cab in Lieu of Low Cab Mounting Height (Approx. 4") for Increased Cooling System Requirements

AIR CONDITIONER {Blend-Air} With Integral Heater & Defroster

Includes

: HEATER HOSES Premium

: HOSE CLAMPS, HEATER HOSE Mubea Constant Tension Clamps

: REFRIGERANT Hydrofluorocarbon HFC-134A

INSTRUMENT PANEL Center Section, Flat Panel

WINDOW, POWER (4) And Power Door Locks, Front and Rear Doors, Left and Right, Includes Express Down Feature

HVAC FRESH AIR FILTER

KEYLESS ENTRY SYSTEM REMOTE With Panic and Auxiliary Buttons, Includes One Key Fob (Transmitter)

FRESH AIR FILTER Attached to Air Intake Cover on Cowl Tray in Front of Windshield Under Hood

LOW WASHER FLUID INDICATOR

CAB INTERIOR TRIM Premium; for Crew Cab

Includes

: "A" PILLAR COVER Molded Plastic

: CAB INTERIOR TRIM PANELS Cloth Covered Molded Plastic, Full Height; All Exposed Interior Sheet Metal is Covered Except for the Following: with a Two-Man Passenger Seat or with a Full Bench Seat the Back Panel is Completely Void of Covering

: CAB SOUND INSULATION Includes Dash and Engine Cover Insulators

: CONSOLE, OVERHEAD Molded Plastic; With Dual Storage Pockets with Retainer Nets, CB Radio Pocket, Speakers, and Reading Lights

: COURTESY LIGHT (4) Mounted In Front and Rear Map Pockets - Left and Right Sides

: DOOR TRIM PANELS with Cloth Insert on Bolster Driver and Passenger Doors

: FLOOR COVERING Rubber, Black

: GAUGE, TEMPERATURE, AMBIENT Includes Wiring and Sensor With Display Unit Mounted in Cluster

: HEADLINER Soft Padded Cloth

: INSTRUMENT PANEL TRIM Molded Plastic with Black Center Section

Description

: STORAGE POCKET, DOOR (2) Molded Plastic (Carpet Texture), Full-Length; Driver and Passenger Doors
: SUN VISOR (3) Padded Vinyl: 2 Moveable (Front-to-Side) Primary Visors, Driver Side with Vanity Mirror and Toll Ticket Strap, plus 1 Auxiliary Visor (Front Only), Driver Side

CAB REAR SUSPENSION Air Bag Type

SUNSHADE, EXTERIOR Aerodynamic, Painted Roof Color; Includes Integral Clearance/Marker Lights

WHEELS, FRONT DISC; 22.5" Painted Steel, 2 Hand Hole, 10 Stud (285.75MM BC) Hub Piloted, Flanged Nut, Metric Mount, 8.25 DC Rims; With Steel Hubs

Includes

: PAINT IDENTITY, FRONT WHEELS White

Notes

: Compatible Tire Sizes: 11R22.5, 12R22.5, 255/70R22.5, 255/80R22.5, 265/75R22.5, 275/70R22.5, 275/80R22.5, 295/75R22.5, 295/80R22.5

WHEELS, REAR DUAL DISC; 22.5" Painted Steel, 2 Hand Hole, 10-Stud (285.75MM BC) Hub Piloted, Flanged Nut, Metric Mount, 8.25 DC Rims; With Steel Hubs

Includes

: PAINT IDENTITY, REAR WHEELS White

Notes

: Compatible Tire Sizes: 11R22.5, 12R22.5, 255/70R22.5, 255/80R22.5, 265/75R22.5, 275/70R22.5, 275/80R22.5, 295/75R22.5, 295/80R22.5

WHEEL SEALS, FRONT {International} Oil-Lubricated Wheel Bearings

WHEEL BEARING, FRONT, LUBE {EmGard 50W} Synthetic Oil

BDY INTG, REMOTE POWER MODULE Mounted Inside Cab behind Driver Seat; Up to 6 Outputs & 6 Inputs, Max. 20 amp. per Channel, Max. 80 amp Total (Includes 1 Switch Pack With Latched Switches)

(2) TIRE, FRONT 11R22.5 HSL2 ECO PLUS (CONTINENTAL) 500 rev/mile, load range G, 14 ply

(4) TIRE, REAR 11R22.5 HSL2 ECO PLUS (CONTINENTAL) 500 rev/mile, load range G, 14 ply

Services Section:

SRV CONTRACT, EXT ENGINE {Navistar} To 48-Month/125,000 Miles (200,000 km), 4500 Hours; Includes Engine, Engine Electronics and Injectors; for MaxxForce 9 Engines

<u>Description</u>	(US DOLLAR)	<u>Price</u>
Factory List Prices:		
Product Items	\$120,509.00	
Service Items	\$4,000.00	
Total Factory List Price Including Options:		\$124,509.00
Freight	\$2,075.00	
Total Freight:		\$2,075.00
Total Factory List Price Including Freight:		\$126,584.00

Please feel free to contact me regarding these specifications should your interests or needs change. I am confident you will be pleased with the quality and service of an International vehicle.